

Technical specifications

OTDR				
Model	OTDR-4000S	OTDR-4000D	OTDR-4000F1(live test)	OTDR-4000F2(live test)
Type	G.652 SM		G.652 SM	
Wavelength	1550nm	1310nm/1550nm	1310nm	1550nm
Dynamic Range	24dB	26dB/24dB	26dB	24dB
Event Blind Zone	2.5m			
ATT Blind Zone	8m			
Test Range	500m/1km/2km/4km/8km/16km/32km/64km/100km			
Pulse Width	3ns/5ns/10ns/20ns/30ns/50ns/80ns/160ns/320ns/500ns/800ns/1μs/2μs/3μs/5μs/8μs/10μs/20μs			
Ranging Accuracy	± (1m+Sample interval+0.005% × Test distance)			
Linearity	≤0.05dB/dB			
Sample Points	16k~128k			
Sample Resolution	0.05m~8m			
Loss Resolution	0.001dB			
Loss Threshold	0.20dB			
Range Resolution	0.001m			
Refractive Index	1.00000~2.00000			
Reflection Accuracy	±3dB			
File Format	SOR Standard File Format			
Loss Analysis	4-point method /5-point method			
Laser Safety Level	Class II			
Connector	FC/UPC (Interchangeable SC, ST)			
Refresh Rate	3Hz (Typ.)			
Multitasking	Support			

OPM

Wave Range	800nm~1700nm
Calibration Wave	850/980/1300/1310/1490/1550/1625/1650nm
Test Range	-70~+10dBm/-50~+26dBm
Resolution	0.01dB
Uncertainty	±5%
Frequency Identification	CW/270/330/1k/2kHz(Use inner LS)
Connector	Universal FC/SC/ST

Wave Recognition Support

VFL

Wavelength	650nm±20nm
Output Power	≥10mW
Mode	CW/1Hz/2Hz
Connector	FC/UPC (Interchangeable SC, ST)
Laser Safety Level	Class III

LS

Wavelength	Consistent with OTDR
Laser Type	FP-LD
Power	≥-5dBm
Stability	CW, ±0.5dB/15min (After 15min of preheating)
Connector	FC/UPC (Interchangeable SC, ST)
Mode	CW/270Hz/330Hz/1kHz/2kHz
Wave Recognition	Support

Optical Loss Test

Wavelength	Consistent with LS
IL Test	Support

RJ45 Cable Tracker

Mode	Digital tracking
Distance	≥300m
Online/Line Pair Tracking	Support

RJ45 Cable Length

Test Distance	≥300m
---------------	-------

Others

Display	4.3 inches 800×480 IPS TFT - LCD Multi touch capacitive touch screen
---------	---

Power Supply	AC/DC adapter: input:100V~240V, 50/60Hz, 0.6A output:5V, 2A, Lithium battery:3.7V, 4000mAh
--------------	---

Battery Working	Continuous test>12 h
-----------------	----------------------

Data Storage	Internal storage:8GB, ≥20 thousand curves
--------------	---

Data Interface	USB Type C
----------------	------------

Working Temperature	-10°C~+50°C
---------------------	-------------

Storage Temperature	-40°C~+70°C
---------------------	-------------

Relative Humidity	0~95% Non Condensing
-------------------	----------------------

Weight	≤0.5kg (Battery included)
--------	---------------------------

Size	173mm×109mm×45mm
------	------------------

Standard configuration: Auto OTDR, expert OTDR, event map, OPM, LS, VFL, RJ45 cable tracker(Including line finder), RJ45 cable sequence, RJ45 cable length, end face detection(Optional), flashlight,optical loss test

注:OTDR-4000F1 can test fiber with 1490/1550nm signal (power ≤-5dBm)
OTDR-4000F2 can test fiber with 1310/1490nm signal (power ≤-5dBm)

Configuration list

Host(Battery included), Adapter, Data Line, 8G TF card(built-in OTDR, Analysis software/User's Manual), User's Manual, SC/UPC, Qualification Certificate/ Service Guarantee Card, Calibration Certificate, Clean Cotton Slices, Instrument Backpack

OTDR-4000 Mini OTDR

Product overview



OTDR-4000 Mini Pro series OTDR adopts 4.3-inch capacitive touch screen. It integrates 12 functions, such as auto OTDR, expert OTDR, event map, OPM, RJ45 cable tracker, and "computer level" file management to meet various test requirements in different occasions. OTDR has a maximum dynamic range of 26dB, 8G memory, and can store more than 200,000 curves; it is equipped with 4000mAh high-density polymer lithium battery, intelligent power saving management, measuring time of more than 8 hours, and supporting power supply and charging of the power bank.

OTDR-4000 series are used to measure the length, loss, connection quality and other parameters of optical fiber. It is widely used in FTTX, secondary backbone network engineering construction, maintenance and emergency repair test, and production measurement of optical fiber and cable.

Product features

- Expert OTDR: Professional measurement, curve/list/map are displayed simultaneously
- Auto OTDR: no complex settings, one key test
- OPM supports CW/270/330/1k/2kHz frequency identification
- VFL and LS can run in the background, multi task can be operated simultaneously
- LS supports CW/ modulation mode output with adjustable output power
- RJ45 cable tracker of digital radar, stronger anti-jamming ability
- Auto OTDR, expert OTDR, event map, OPM, LS, VFL, RJ45 cable tracker, RJ45 cable sequence, RJ45 cable length, end face detection, flashlight optical loss test
- RJ45 cable sequence/ cable length test, up to 300m
- One click screen capture, easy to save the interface



Multi-touch Support gesture zoom in and out curve



End face detection HD imaging



Optical loss test Insertion loss test



File management Computer level management



20h standby Ultra wide operating temperature

Concentrative, Dedicated, Professional