

INTELLIGENT PLUS SERIES

4" Industrial Thermal Transfer Barcode Printer



KEY FEATURES

- 400 MHz 32-bit ARM9 processor with 128 MB SDRAM or 256 MB SDRAM, 128 MB Flash memory or 256 MB Flash memory
- Internally scalable true type font engine
- Firmware emulates TSPL, EPL, ZPL, ZPL II, DPL.
- Bartender® Free Windows drivers and label design software (available via download)
- Provide Windows printer utility, Windows SDK and Android SDK.



INTELLIGENT PLUS SERIES

MODEL	GI-2408T PLUS	GI-3406T PLUS	GI-2410T PLUS	GI-3407T PLUS
Grade	Standard	Standard	Empower	Empower
Resolution	8dots/mm (203DPI)	12dots/mm (300DPI)	8dots/mm (203DPI)	12dots/mm (300DPI)
Printing Method	Thermal Transfer & Direct Thermal			
Max. print speed	203mm(8")/second	152mm(6")/second	254mm(10")/second	177.8mm(7")/second
Max. print width	104 mm (4.1")	108.4 mm (4.27")	104 mm (4.1")	108.4 mm (4.27")
Max. print length	2,286mm (90")	1,016mm (40")	2,286mm (90")	1,016mm (40")
CPU	400MHZ, 32-bits, ARM9			
Memory RAM	128 MB SDRAM		256 MB SDRAM	
Memory ROM	128 MB Flash Memory		256 MB Flash Memory	
Interface	<ul style="list-style-type: none"> •USB 2.0 High Speed 480Mbps •USB Host 2.0, for scanner or PC keyboard •RS-232 		<ul style="list-style-type: none"> •Internal Ethernet 10/100Mbps •Internal Bluetooth 4.0 (factory option) •Internal WiFi (factory option) 	
Real Time Clock	Standard			
Buzzer	Standard			
Dealer options	<ul style="list-style-type: none"> •Guillotine cutter (full cut or partial cut) 		<ul style="list-style-type: none"> •Peeler 	<ul style="list-style-type: none"> •Tear paper
Sensors	<ul style="list-style-type: none"> •Gap transmissive sensor (position adjustable) •Black mark reflective sensor (position adjustable) •Head open sensor 		<ul style="list-style-type: none"> •Ribbon end sensor •Label end sensor •Label begin sensor 	<ul style="list-style-type: none"> •Ribbon out sensor
Power	Internal universal switching power supply Input: AC 200-240V, 1.5A, 50-60Hz, Output : DC 24V, 5A, 120W			
User Interface	<ul style="list-style-type: none"> •1 power switch •2 buttons (Feed & Pause) •4 LEDs (Online, Error, Ribbon, Communication status) 		<ul style="list-style-type: none"> •1 power switch •1 buttons (Feed) •1 LEDs(Online, Error, Ribbon status) •LCD, TFT LCD 4.3" 16 bits Color, 272 x 480 pixels, with back lights 	
Internal fonts	<ul style="list-style-type: none"> •8 alpha-numeric bitmap fonts •True type font engine (need download scalable font file) 			
RFID	RFID front			
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Pleassy, PostCode, Telepen			
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix			
Rotation	Font and barcode support 0, 90, 180, 270 degree			
Printer language	Compatible to TSPL, EPL, ZPL, ZPL II, DPL			
Ribbon	450 M long, max. OD 105 mm, 1" core (ink coated outside)			
Ribbon width	Max.110mm (4.3")			
Media type	Continuous, die-cut, black mark, fan-fold (outside wound)			
Media width	20~ 120 mm (0.78" ~ 4.72")			
Media thickness	0.06~0.254mm (2.36 ~ 10 mil)			
Media core diameter	25.4 mm ~ 76.2 mm (1" ~ 3")			
Label roll capacity	203 mm (8") OD			
Label length	5~2,286 mm (0.2" ~ 90")	5~1,016 mm (0.2" ~ 40")	5~2,286 mm (0.2" ~ 90")	5~1,016 mm (0.2" ~ 40")
Physical dimension	260mm (W) * 335mm (H) * 439mm (D)			
Net Weight	12.8kg			

Enclosure

Die-cast based print mechanism/Metal cover with large clear media view window

Safety regulation

FCC Class A, CE Class A, CCC, BIS, CB

Environmental concern

Comply with RoHS, REACH, WEEE

Ribbon

450 M long, max. OD 105 mm, 1" core (ink coated outside)

Environment condition

Operation: 5 ~ 40°C, 25 ~ 85% non-condensing
Storage: -40 ~ 60°C, 10 ~ 90% non-condensing

Accessories

- Windows labeling software CD disk
- Quick start guide
- USB cable
- Power cord
- 1" ribbon spindle x 2 for 450M ribbon

Ribbon width

Max.115mm (4.5")