

# E2001

Thermal  
Receipt Printer

G  
A  
-  
E  
2  
0  
0  
1



## FEATURES

- 200mm/s printing speed
- The printing command protocol is based on the ESC/POS standard mode
- Support CODE128, QRCODE and other barcode printing
- Support character enlargement, rotation, inversion and reverse whitening and paper-end reprint functions
- Equipped with USB, Ethernet port, RJ11 cash box communication interface
- Suitable for restaurants, takeout orders, stores, supermarkets, hotels and other scenarios and applications



MODEL	GA-E2001
Level	Standard
Resolution	8dots/mm(203DPI)
Printing Method	Direct Thermal
Print head	ROHM/KAITONG
Print speed	200mm/sec
Print width	72mm
CPU	144MHZ, 32 Bit Cortex-M4
Memory RAM	64K bytes
Memory ROM	256K bytes
Memory FLASH	32M bytes
Indicator light	1.FEED light 2. Error light (two lights)
Interface	1.USB+RJ11 CashDrawer 2.ETH+RJ11 CashDrawer 3.USB+ETH+RJ11 CashDrawer
Buzzer	Standard
Sensors	Reflective sensor
Paper cutting	Auto Cutter/Tear bar
Print head life	150KM
Cutter life	1.5 million times
Printer language	Simplified Chinese, Traditional Chinese, Japanese, Korean, ANK Character Set
Media type	Thermal paper
Media width	58/80mm
Physical dimension	130mm (D) x 161mm (W) x 126mm(H)
Net Weight	1kg



# GA-E2001



## Safety regulation

FCC Class A,  
CE Class A, CCC,

## Environmental concern

Comply with RoHS

## Accessories

- thermal paper(80mm\*8m)
- Power supply adapter
- USB cable