

EL5610-08F EPON OLT

Product Overview:

EL5610-08F is a field-OLT switching equipment, providing 8* EPON OLT interface, 4* 10000Base-SR / LR / ER interface, 1* GE inband. EL5610-08F OLT adopts industry-leading technology and it supports SLA and DBA. Up to 1:64 split ratio, EL5610-08F supports different types of ONU hybrid network, minimize the operator's investment.

For its cost-effective, EL5610-08F can be able to apply to operator's network FTTH access, video surveillance network, enterprise LAN, web of things and other network applications.



Product Specification:

Item	EL5610-08F
Switching Capacity	108Gbps
Forwarding Capacity(Ipv4/Ipv6)	80Mpps
Service Port	8*PON port, 4*10000Base-SR/LR/ER interface, 1*1000GE interface
Redundancy Design	single power supply, dual power supply, dual AC input, dual DC input and AC + DC input
Power Supply	AC: input 100~264V 47/63Hz; DC: input -36V~-72V;
Power Consumption	≤78W
Dimensions (Width x Depth x Height)	385X307X180
Weight (Full-Loaded)	≤10kg

Environmental Requirements	<p>Working temperature: -20°C~70°C</p> <p>Storage temperature: -40°C~85°C</p> <p>Relative humidity: 10%~90%, no condensation</p>
----------------------------	--

Service Features:

Item	EL5610-08F	
PON Features	<p>IEEE 802.3ah EPON</p> <p>China Telecom/Unicom EPON</p> <p>Maximum 20 Km PON transmission distance</p> <p>Each PON port supports the max. 1:64 splitting ratio</p> <p>Uplink and downlink triple churning encrypted function with 128Bits</p> <p>Standard OAM and extended OAM</p> <p>ONU batch software upgrade, fixed time upgrade, real time upgrade</p> <p>PON transmit and inspect receiving optical power</p> <p>PON port optical power detection</p>	
L2 Features	MAC	<p>MAC Black Hole</p> <p>Port MAC Limit</p> <p>16K MAC address</p>
	VLAN	<p>4K VLAN entries</p> <p>Port-based/MAC-based/protocol/IP subnet-based</p> <p>QinQ and flexible QinQ (StackedVLAN)</p> <p>VLAN Swap and VLAN Remark</p> <p>PVLAN to realize port isolation and saving public-vlan resources</p> <p>GVRP</p>
	Spanning Tree	<p>STP/RSTP/MSTP</p> <p>Remote loop detecting</p>
	Port	<p>Bi-directional bandwidth control</p> <p>Static link aggregation and LACP(Link Aggregation Control Protocol)</p> <p>Port mirroring</p>
Security Features	User's Security	<p>Anti-ARP-spoofing</p> <p>Anti-ARP-flooding</p> <p>IP Source Guard create IP+VLAN+MAC+Port binding</p> <p>Port Isolation</p> <p>MAC address binding to the port and MAC address filtering</p> <p>IEEE 802.1x and AAA/Radius authentication</p>
	Device Security	<p>Anti-DOS attack(such as ARP, Synflood, Smurf, ICMP attack), ARP detection, worm and Msblaster worm attack</p> <p>SSHv2 Secure Shell</p> <p>SNMP v3 encrypted management</p> <p>Security IP login through Telnet</p> <p>Hierarchical management and password protection of users</p>
	Network Security	<p>User-based MAC and ARP traffic examination</p> <p>Restrict ARP traffic of each user and force-out user with abnormal ARP traffic</p>

		<p>Dynamic ARP table-based binding</p> <p>IP+VLAN+MAC+Port binding</p> <p>L2 to L7 ACL flow filtration mechanism on the 80 bytes of the head of user-defined packet</p> <p>Port-based broadcast/multicast suppression and auto-shutdown risk port</p> <p>URPF to prevent IP address counterfeit and attack</p> <p>DHCP Option82 and PPPoE+ upload user's physical location Plaintext authentication of OSPF, RIPv2 and BGPv4 packets and MD5 cryptograph authentication</p>
Service Features	ACL	<p>Standard and extended ACL</p> <p>Time Range ACL</p> <p>Flow classification and flow definition based on source/destination MAC address, VLAN, 802.1p, ToS, DiffServ, source/destination IP(IPv4/IPv6) address, TCP/UDP port number, protocol type, etc</p> <p>packet filtration of L2~L7 deep to 80 bytes of IP packet head</p>
	QoS	<p>Rate-limit to packet sending/receiving speed of port or self-defined flow and provide general flow monitor and two-speed tri-color monitor of self-defined flow</p> <p>Priority remark to port or self-defined flow and provide 802.1P, DSCP priority and Remark</p> <p>CAR(Committed Access Rate), Traffic Shaping and flow statistics</p> <p>Packet mirror and redirection of interface and self-defined flow</p> <p>Super queue scheduler based on port or self-defined flow. Each port/flow supports 8 priority queues and scheduler of SP, WRR and SP+WRR.</p> <p>Congestion avoid mechanism, including Tail-Drop and WRED</p>
	IPv6	<p>SA/DA Classification</p> <p>MLD Snooping</p>
	Multicast	<p>IGMPv1/v2/v3</p> <p>IGMPv1/v2/v3 Snooping</p> <p>IGMP Filter</p> <p>MVR and cross VLAN multicast copy</p> <p>IGMP Fast leave</p> <p>IGMP Proxy</p> <p>PIM-SM/PIM-DM/PIM-SSM</p> <p>PIM-SMv6、PIM-DMv6、PIM-SSMv6</p> <p>MLDv2/MLDv2 Snooping</p>
Reliability	Loop Protection	<p>EAPS and GERP (recover-time <50ms)</p> <p>Loopback-detection</p>
	Link Protection	<p>FlexLink (recover-time <50ms)</p> <p>RSTP/MSTP (recover-time <1s)</p> <p>LACP (recover-time <10ms)</p> <p>BFD</p>
	Device Protection	<p>VRRP host backup</p> <p>1+1 power hot backup</p>

Maintenance	Network Maintenance	Port real-time, utilization and transmit/receive statistic based on TGLnet RFC3176 sFlow analysis LLDP 802.3ah Ethernet OAM RFC 3164 BSD syslog Protocol Ping and Traceroute
	Device Management	CLI, Console port, TGLnet and WEB SNMPv1/v2/v3 RMON (Remote Monitoring)1,2,3,9 groups MIB NTP GN.Link II Server NGBNView