

L2TP Configuration

XXXX Communication Technology Co., Ltd

Tel: (86)

Fax: (86)

URL:

Email:

All rights reserved. Printed in the People's Republic of China.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written consent of XXXX Communication Technology Co., Ltd.

XXXX makes no representations or warranties with respect to this document contents and specifically disclaims any implied warranties of merchantability or fitness for any specific purpose. Further, XXXX reserves the right to revise this document and to make changes from time to time in its content without being obligated to notify any person of such revisions or changes.

XXXX values and appreciates comments you may have concerning our products or this document. Please address comments to:

XXXX Communication Technology Co., Ltd

Tel: (86)

Fax: (86)

URL:

Email:

All other products or services mentioned herein may be registered trademarks, trademarks, or service marks of their respective manufacturers, companies, or organizations.

Contents

Chapter 1

L2TP Configuration.....

1

1.1

L2TP Overview.....

1

1.2

L2TP Configuration

1

1.2.1

Configure L2-Tunnel Packet

1

1.2.2

Advanced L2TP Configuration

2

1.2.3


L2TP Monitor and Maintenance

2

Chapter 1 L2TP Configuration

1.1 L2TP Overview

L2TP (Layer 2 Tunneling Protocol) is a Layer 2 tunneling technology, L2TP enables Layer 2 protocol packets from geographically dispersed customer networks to be transparently transmitted over specific tunnels across a service provider network.



Pictuer 1-1. L2TP application scenario

With L2TP, Layer 2 protocol packets from customer networks can be transparently transmitted in the service provider network:

1. After receiving a Layer 2 protocol packet from User A network 1, PE 1 in the service provider network encapsulates the packet, replaces its destination MAC address with a specific multicast MAC address, and then forwards the packet in the service provider network.
2. The encapsulated Layer 2 protocol packet (called bridge protocol data unit, BPDU for short) is forwarded to PE 2 at the other end of the service provider network, which de-encapsulates the packet, restores the original destination MAC address of the packet, and then sends the packet to User A network 2.

1.2 L2TP Configuration

1.2.1 Configure L2-Tunnel Packet

Table 1-1 Configure the L2-tunnel packet

Operation	Command	Remarks
Enter global configuration mode	configure terminal	-
Enter interface configuration	interface ethernet <i>interface-num</i>	-

mode		
Configure the L2-tunnel packet	l2-tunnel [cdp lacp pagp stp udld vtp]	Required

1.2.2 Advanced L2TP Configuration

By default, L2TP will be up to CPU. This command will configure the rate for up to cpu.

Table 1-2 Advanced L2TP configuration

Operation	Command	Remarks
Enter global configuration mode	configure terminal	-
Configure the rate for up to cpu	l2-tunnel drop-threshold [cdp lacp pagp stp udld vtp] rate	Optional

1.2.3 L2TP Monitor and Maintenance

After finishing above configuration, user can check the configurations by command below.

Table 1-3 L2TP monitor and maintenance

Operation	Command	Remarks
Show L2TP configuration	show l2-tunnel interface [ethernet interface-num]	On any configuration mode
Show the rate for up to cpu	show l2-tunnel drop-threshold	On any configuration mode