



**Shenzhen Yuhengda Technology Co., Ltd.**

10th floor B block, QingHu technology Park, QingXiang Road, LongHua District, ShenZhen, CN  
+86-755-28483853 Mobile: +86 13760364456(Wechat) WhatsApp/Skype: +86 13760364456  
Contact: Zoe Zhou Email: zoe@yhdaa.com

---

## **YHD-1100D+**

### **2D Wired Barcode Scanner with Stand**



#### **1.Features**

- \* Factory direct sale, Low price high performance.
- \* No driver needed, plug and play.
- \* Support reading bar codes from screen.
- \* Applying CMOS image technology, easy to scan.
- \* Powerful decode ability, fast scanning 1D/2D barcodes.
- \* Support the multinational language keyboard.
- \* Supports Handheld / Continuous / Auto-Induction , 3modes for option.
- \* Dopt a highly integrated design, high quality shell, have IP45 protection grade.
- \* Support connection with computer, laptop. Compatible Operating System for Linux, Windows XP,7,8,10.
- \* Application fields:Supermarket, Retail, Warehouse, Logistic, Library, Medical etc.

## 2. Technical parameters

Product Specification: YHD-1100D+ 2D Wired Barcode Scanner with Stand		
<b>Scanner parameters:</b>		
CPU: ARM 32-bit Cortex		Sensor: CMOS 640*480
Resolution : 4mil		Light aimer: 624nm LED
Printing Contract : ≥25%		Material: ABS+PC
Indication: Buzzer & LED		Drop test : 2m
Decoding speed: 500scans/sec		Anti inference: 0-100000Lux Max
Button life : 5000,000 times		Voltage:5V DC
Depth of Field	13mil-EAN13	40-250mm
	4mil-code39	50-90mm
	20mil-QR	40-290mm
	10mil-PDF417	40-260mm
Decode Capability: 1D: UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Standard 2 of 5, Coda bar, MSI Plessey, RSS, Codabar, ISBN、ISSN、GS1 DataBar(RSS14)etc. 2D: QR Code, Data Matrix, PDF417, Aztec code, Maxicode, etc.		
Trigger Mode: Handheld,Continuous, Auto-Induction		
Scanning angle: Angle of rotation360°, inclination± 65°,declination ± 60°		
Current: 80mA(working current), 30mA(standby current )		
Temperature: -20℃-50℃(Working) -40℃-60℃(Storage)		
Interface : TTL、RS232、KBW、USB		
Operating Humidity: 5 - 95% (non-condensing)		
Certificate : CE, FCC, RoHS, IP54		

## 3. Packaging Details

- \* Standard List: Scanner \*1, USB Cable \*1, Manual \*1, Stand \*1, Box \*1.
- \* Single Package Size: 185\*120\*86mm
- \* Single Gross Weight: 0.4kg
- \* 30pcs/CTN Carton Size: 438\*380\*380mm
- \* 30pcs/CTN Carton G.W.:13Kg, N.W:11Kg

#### 4. Product Pictures

