

5G Mobile Hotspots Specification



Specifications

Basic configuration	Product Model	KT-M3A
	OS Version	Android™ 11.0
	CPU Type	MT6877(MTK900), 6nm, 2*A78 (2.4GHz) +6*A55(2.0GHz), GPU: Mali OTR MC4
	LCD	Not Support
	TP	Not Support
	LED	1*5G signal, 1*4G signal, 1*Wifi, 1*Power
	RAM	2GB
	ROM	32GB
Networks/Cellular	Protocal	3GPP Rel.15, 5G NR, SA/NSA, Sub 6G/LTE Category 18
	Bands	[CN] 5G NR: N1/N3/N5/N8/N28A/N41/N77/N78 (N41/N77/N78 UL 2MIMO) 4G FDD: B1/B3/B5/B8/B28 4G TDD: B34/B38/B39/B40/B41 [EAU] 5G NR: N1/N3/N5/N8/N28A/N41/N77/N78 (N41/N77/N78 UL 2MIMO) 4G FDD: B1/B3/B5/B8/B28 4G TDD: B34/B38/B39/B40/B41 [LAM] 5G NR: N2/N5/N8/N28/N41/N66/N77/N78 (N41/N77/N78 UL 2MIMO) 4G FDD: B2/B5/B7/B8/B28/B66 4G TDD: B42/B43
	Throughput	NR: Downlink/Uplink up to 2.77Gbps/1.25Gbps LTE: Downlink/Uplink up to 1.2Gbps/150Mbps WCDMA: Downlink/Uplink up to 42.2Mbps/11.5Mbps
	Antenna	4*4 MIMO
WiFi	Bands	2.4G, 5.8G, DBSC(2*2), DBDC (1*1)
	Protocal	802.11 a/b/g/n/ac/ax, WIFI6
	Throughput	802.11a: Up to 54Mbps 802.11b: Up to 11Mbps 802.11g: Up to 54Mbps 802.11n: Up to 300Mbps 802.11ac:Up to 866Mbps 802.11ax:Up to 1201Mbps
	Antenna	2*2
	Users	16 users

Interface	Button	1*Power, 1*Reset
	SIM card	Single SIM card, hot plugging supported
	USB Interface	Type-C 2.0, 5V/2A
	Charger	5V/2A
Battery	Type	Lithium-ion polymer battery
	Capacity	10000mAh
General	Dimensions	130 x 82 x 18.5 mm (customized available)
	Weight	222g
	Working Temperature	0°C-55°C
	Storage Temperature	-20°C-70°C
	Storage humidity	5%-95%

Shenzhen Jintaiyi Electronic Co., Ltd.

12-A, Building E4, TCL International E-City, Zhongshanyuan Rd, Nanshan, Shenzhen, Guangdong Province, China, 518051

Email: info@kingtoptec.com

<https://www.kingtoptec.com/>

Copyrights © 2023 Kingtop Corp. All Rights Reserved

*Product specifications and availability are subject to change without notice.